

VISA 2

The New GMI "Low Cost" Confined Space Monitor

Reach for your
CONFINED SPACE
LIFESAVER



Your robust, lightweight, low cost instrument ensuring
Safe Entry into and Safe Exit from confined spaces

- Easy to Use
- Brilliant Visual Alarm – 360° distinct alarm level, flash rates prioritised
- Ultra loud Audible Alarm – Penetrating 95dBA
- Specifically designed for pre-entry and post-entry applications.
- Lightweight / Hi-Impact resistant casing
- International Certification and Conformance
- Datalogging Capability



IF YOU REQUIRE A QUOTATION FOR ANY PARTICULAR INSTRUMENT AND ASSOCIATED ACCESSORIES, PLEASE COMPLETE ORDERING REQUIREMENT COLUMN THEN ACCESSORIES TICK BOXES

Ordering Requirement

Please note that VISA 2 is only available as a non-pumped instrument and with the following sensor / battery pack configurations.

All options include datalogging as standard.

Instrument c/w Listed Sensor / Battery Types	Part No.	
LEL / O ₂ (Alkaline)	66901	<input type="checkbox"/>
LEL / O ₂ (NiMH)	66902	<input type="checkbox"/>
LEL / O ₂ / H ₂ S (Alkaline)	66903	<input type="checkbox"/>
LEL / O ₂ / H ₂ S (NiMH)	66900	<input type="checkbox"/>
LEL / O ₂ / CO (Alkaline)	66904	<input type="checkbox"/>
LEL / O ₂ / CO (NiMH)	66905	<input type="checkbox"/>
LEL / O ₂ / H ₂ S / CO (Alkaline)	66906	<input type="checkbox"/>
LEL / O ₂ / H ₂ S / CO (NiMH)	66907	<input type="checkbox"/>

Notes:

- Alkaline (Dry Cell) battery pack provides up to 24 hours operation.
- Rechargeable (NiMH) battery pack provides up to 20 hours operation.

Sensor	Range
LEL	0 - 100% LEL
O ₂	0 - 25%
H ₂ S	0 - 100 PPM
CO	0 - 1000 PPM

Each instrument is supplied complete with User Handbook, Battery / Sensor Grille Key, Inlet Filter Key, (integral) Belt Clip and Calibration Certificate. If a (NiMH) rechargeable battery pack is selected, a Standard Charger (as shown below) is also included.



Accessories

Standard Accessories	Part No.	
Hand Aspirator c/w 3.0 metres Tygon Tubing & Connector	66478	<input type="checkbox"/>
Neck Harness with Clip	66028	<input type="checkbox"/>
Body Harness	66546	<input type="checkbox"/>
Inlet Nozzle Filter Key (1.5mm.A/F)	66165	<input type="checkbox"/>
Battery / Sensor Grille Key (2mm.A/F)	66166	<input type="checkbox"/>
Instrument Key	66167	<input type="checkbox"/>
Sensor Hydrophobic Filter	66083	<input type="checkbox"/>
In-line Hydrophobic Filter c/w Fittings	66485	<input type="checkbox"/>
In-line Hydrophobic Filter	66484	<input type="checkbox"/>
Alkaline (Dry Cell) Battery Pack	66538	<input type="checkbox"/>
Rechargeable (NiMH) Long Duration Battery Pack	66548	<input type="checkbox"/>
CD ROM (Instruction Manual) Configuration and Field Calibration	66203	<input type="checkbox"/>
Standard Chargers	Part No.	
Charger / Universal PSU	66140	<input type="checkbox"/>
5-Way Standard Charger c/w Universal PSU	66200	<input type="checkbox"/>
10-Way Standard Charger c/w Universal PSU	66207	<input type="checkbox"/>
12V / 24V Vehicle Charger Lead	66206	<input type="checkbox"/>
Communications Options	Part No.	
Data Downloading Software c/w Interface Adaptor & User Instructions	66208	<input type="checkbox"/>
Data Downloading Software c/w Charger (Universal PSU) ; Interface Adaptor & User Instructions	66300	<input type="checkbox"/>
VISACAL (Calibration) Software c/w Interface Adaptor & User Instructions	66445	<input type="checkbox"/>
VISACAL (Calibration) Software c/w Charger (Universal PSU) ; Interface Adaptor & User Instructions	66448	<input type="checkbox"/>
USB Adaptor (for above items)	66209	<input type="checkbox"/>

Note: The Interface Adaptor replaces the battery pack while calibrating or downloading data from the instrument, therefore a standard charger, as listed, is required to power the instrument. If a charger is required, order as appropriate from above list



Specifications

Physical Properties

Weight: 0.4 kg
Dimensions: 140 x 85 x 45 mm

Environment

Temperature Limits -20°C to +50°C
Humidity: 0 to 95% R.H. non-condensing

Performance

Complies with:
IEC 61779 (Flammable)
EN 50104 (Oxygen)
EN 45544 (Toxic)

Certification

ATEX II 1 G EEx ia IIB T3
DEMKO03 ATEX 133803X

or

ATEX II 2 G EEx ia d IIC T3
Sira 05 ATEX 2295 (Rechargeable)

or

ATEX II 2 G EEx iad IIC T4
Sira 05 ATEX 2295 (Alkaline)

(European Mark of Conformity)

Classified as to intrinsic safety only:

UL 913 Class I, Div 1 Groups ABCD

EC Type Examination Certificate MED



GMI HEAD OFFICE:
Inchinnan Business Park,
Renfrew, PA4 9RG,
Scotland, U.K.
Tel: +44 (0) 141-812 3211
Fax: +44 (0) 141-812 7820

CoGDEM
The Council of Gas Detection and
Environmental Monitoring
www.gmiuk.com
e-mail: sales@gmiuk.com



GMI SERVICE CENTRE:
25 Cochran Close,
Milton Keynes, MK8 OAJ,
England, U.K.
Tel: +44 (0) 1908 568867
Fax: +44 (0) 1908 261056

As an ISO 9001 approved company, GMI Ltd's quality assurance programmes demand the continuous assessment and improvement of all GMI products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representative if you require more details.

Copyright © Gas Measurement Instruments Ltd. 2008. All rights reserved.

Part Number 99317 Issue 2 17/09/08